

Date received: 07/03/17

Date of issue: 18/04/17

Report consists of 1 test report.

Defects before testing: None

Sample name: Armchair FLASH-R

SAVANS PLASTIK SAN. VE. TIC. A.S.
BEYSAN SAN. SIT. BIRLIK CAD. NO: 18-BEY.
34524 ISTANBUL ()
TR – TURKEY

SAMPLE N° 229732 S

Overall dimensions: 570 x 560 x 850 (h) mm

List performed tests:

1. Requisiti generali di sicurezza EN 581-1:2017



This document replaces the previous one with the same reference and with date of issue 06/04/17.

This document is validated by digital signature and time stamping in accordance with the Italian laws and the European Directives which regulate the electronic signature systems.

Managing Director
Dr. Andrea Giavon

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise stated, sampling has been carried out by the orderer.

SAMPLE N° 229732 S

Date of issue: 18/04/17
Sample weight: Not determined
Sample name: Armchair FLASH-R



Side view



Rear view



Bottom view

TEST REPORT

229732 / 1 S

Date received: 07/03/17

Date of test: 05/04/17

Date of issue: 18/04/17

Sample name: Armchair FLASH-R



SAVAS PLASTIK SAN. VE. TIC. A.S.
BEYSAN SAN. SIT. BIRLIK CAD. NO: 18-BEY.
34524 ISTANBUL
TR - TURKEY

Requisiti generali di sicurezza EN 581-1:2017

5.1 General:

Requirement	Observed	Remarks
Edges of seat, back rest and arm rests rounded and chamfered	Yes	None
All other parts: free from burrs, sharp edges and sharp points.	Yes	None
Movable and adjustable parts designed so that injuries and inadvertent operation are avoided	Not present	None
Any load bearing part of furniture not come loose unintentionally	Yes	None
Lubricated parts are protected	Not present	None

5.2 Tubular components:

Requirement	Observed	Remarks
Absence of tubular components with diameter > 7 mm and < 12 mm with a depth > 10 mm.	Yes	None
Tubulars in contact with the floor are closed. Holes in them are allowed as long as they are < 7 mm or > 12 mm	Yes	None

5.3 Shear and squeeze points:

Requirement	Observed	Remarks
Shear and squeeze points that are created only during adjusting and folding away are acceptable if the user has the control of his/her movements.	Yes	None
Absence of shear and squeeze points, created by parts operated by powered mechanism.	Mechanism not present	None
Absence of shear and squeeze points, created by loads applied during normal use.	Yes	None

Conformity to requirements of clause 5 of standard EN 581-1:2017:

YES

This document replaces the previous one with the same reference and with date of issue 06/04/17.

This document is validated by digital signature and time stamping in accordance with the Italian laws and the European Directives which regulate the electronic signature systems.

Managing Director
Dr. Andrea Giavon

The sample name and, when relevant, its description, are given by the orderer, and CATAS does not assume responsibility on this matter. This test report relates to the sample submitted for the test and no others. Additions, deletions or alterations are not permitted. This test report must always be reproduced in its entirety. Unless otherwise stated, sampling has been carried out by the orderer.