

Report ID:	334553
Date of sample receipt:	26/08/22
Date of issue:	11/10/22

SAVAS PLASTIK SAN. VE. TIC. A.S. BEYSAN SAN. SIT. BIRLIK CAD. NO: 18-BEY. 34524 ISTANBUL TR - TURKEY

Sample name:

MOON C FOLDABLE LEG Q 60

### **SAMPLE N° 334553**

Overall dimensions: Ø 600 x 755 (h) mm

#### List of test reports:

- 1. Outdoor tables: safety requirements EN 581-1:2017 clause 5
- 2. Vertical static load test EN 1730:2012, clause 6.3
- 3. Horizontal fatigue test EN 1730:2012, clause 6.4.2
- 4. Stability under vertical load EN 1730:2012, clause 7.2



This document is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian e ú



Testing site: via Antica, 24/3 33048 San Giovanni al Nat. (UD) tel. +39 0432 747211 lab@catas.com



# TEST REPORT

00-007		
Revision:	0	
Date of sample receipt:	26/08/22	
Date of test:	03/10/22	
Date of issue:	11/10/22	



SAVAS PLASTIK SAN. VE. TIC. A.S. BEYSAN SAN. SIT. BIRLIK CAD. NO: 18-BEY. 34524 ISTANBUL TR - TURKEY

Sample name:

MOON C FOLDABLE LEG Q 60

#### Outdoor tables: safety requirements EN 581-1:2017 clause 5

5.1 General requirements			
Requirements	Observed	Remarks	
Table top: edges are rounded or chamfered	Yes	None	
All other edges: are free from burrs and/or sharp edges	Yes	Sharp edges have been noticed (see image pag 2/2)	
Movable and adjustable parts: are designed so to injuries and inadvertent operation are avoided	Yes	None	
Load bearing part of table: shall not be possible to come loose unintentionally	Yes	None	
Parts which are lubricated: all the parts which are lubricated shall be designed to protect users	1	Parts which are lubricated not present	
5.2 Tubular components			
Ends of hollow tubolar components with $\emptyset \ge 7$ mm and $\le 12$ mm where the accessible depth is $\ge 10$ mm: not present	Yes	None	
Bottom of tubolar legs, holes $\geq$ 7 mm and $\leq$ 12 mm: not present	Yes	None	
5.3.2 Shear and squeeze points under influence of powered mechanisms			
Requirements	Observed	Remarks	
Absence of shear and squeeze points under influence of powered mechanisms	1	Powered mechanisms not present	
5.3.3 Shear and squeeze points during use			
Requirements	Observed	Remarks	
Absence of shear and squeeze points created by forces applied during normal use, see: EN 581-3:2017 - Table 1	Yes	None	

Note:

The test result does not comply with safety requirements of EN 581-1:2017 clause 5

This test report is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian nei 0 SUC



TEST REPORT Date of issue: Sample name: CATAS S.p.A. via Antica, 24/3 33048 San Giovanni al Nat. (UD) +39 0432 747211 - lab@catas.com www.catas.com

MOON C FOLDABLE LEG Q 60

334553 / 1 rev. 0

11/10/22

Testing site: via Antica, 24/3 33048 San Giovanni al Nat. (UD) tel. +39 0432 747211 lab@catas.com





This test report is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian e



Testing site: via Antica, 24/3 33048 San Giovanni al Nat. (UD) tel. +39 0432 747211 lab@catas.com



## TEST REPORT

00-0072		
Revision:	0	
Date of sample receipt:	26/08/22	
Date of test:	03/10/22	
Date of issue:	11/10/22	



Sample name:

#### MOON C FOLDABLE LEG Q 60

SAVAS PLASTIK SAN. VE. TIC. A.S. BEYSAN SAN. SIT. BIRLIK CAD. NO: 18-BEY. 34524 ISTANBUL TR - TURKEY

### Vertical static load test EN 1730:2012, clause 6.3

#### Clause 6.3.1 Vertical static load test on main surface

Test results:

Load application position	Vertical force N	Number of cycles	Remarks
100 mm from the edge of the top, at the middle of the long side	1000	10	No defects
Geometrical centre of the top	1000	10	No defects

Clause 6.3.2 Additional vertical static load test where the main surface has a lenght > 1600mm Test results:

2 Load application positions	Vertical force N	Number of cycles	Remarks
On the longitudinal axis, 400 mm on either side of the transversal axis	/	1	Not applicable

Clause 6.3.3 Vertical static load test on ancillary surface

Test results:

Load application position	Vertical force N	Number of cycles	Remarks
100 mm from the edge of the top, at the middle of the long side	/	/	Not applicable

Note:

The test has been carried out according to Table 1 of EN 581-3:2017 Test level: Contract

The test results comply with strength and durability requirements of EN 581-3:2017 clause 5.2.2 (a,b,c)

This test report is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian nei 0



Testing site: via Antica, 24/3 33048 San Giovanni al Nat. (UD) tel. +39 0432 747211 lab@catas.com



## TEST REPORT

	3345537	3
F	Revision:	0
[	Date of sample receipt:	26/08/22
[	Date of test:	03/10/22
1	Date of issue:	11/10/22
ę	Sample name:	MOON (



MOON C FOLDABLE LEG Q 60

SAVAS PLASTIK SAN. VE. TIC. A.S. BEYSAN SAN. SIT. BIRLIK CAD. NO: 18-BEY. 34524 ISTANBUL TR - TURKEY

### Horizontal fatigue test EN 1730:2012, clause 6.4.2

Test results:

Direction of the force	Specified horizontal force N	Applied horizontal force N	Number of cycles	Load on top kg	Remarks
Longitudinal (Fa)	300	150	20.000	50	No defects
Longitudinal (Fb)	300	150	20.000	50	No defects
Transverse (Fc)	300	150	20.000	50	No defects
Transverse (Fd)	300	150	20.000	50	No defects

Note:

The test has been carried out according to Table 1 of EN 581-3:2017 Test level: Contract

The test results comply with strength and durability requirements of EN 581-3:2017 clause 5.2.2 (a,b,c)

According to EN 1730:2012, horizontal force applied has been reduced to avoid tipping of the table.

This test report is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian e 0



Sample name:

CATAS S.p.A. via Antica, 24/3 33048 San Giovanni al Nat. (UD) +39 0432 747211 - lab@catas.com www.catas.com Testing site: via Antica, 24/3 33048 San Giovanni al Nat. (UD) tel. +39 0432 747211 lab@catas.com



## TEST REPORT

00400074			
Revision:	0		
Date of sample receipt:	26/08/22		
Date of test:	11/10/22		
Date of issue:	11/10/22		



MOON C FOLDABLE LEG Q 60

SAVAS PLASTIK SAN. VE. TIC. A.S. BEYSAN SAN. SIT. BIRLIK CAD. NO: 18-BEY. 34524 ISTANBUL TR - TURKEY

### Stability under vertical load EN 1730:2012, clause 7.2

Type of surface tested: Longest dimension of the table top (L): main surface 600 mm

Test results:

Vertical force N	Remarks
200 N	The table does not tip

Note:

The test has been carried out according to Table 1 of EN 581-3:2017 The test results comply with stability requirements of EN 581-3:2017 clause 5.2.2

This test report is part of a PDF file digitally signed by Franco Bulian.

The managing director Dr. Franco Bulian e 0